Product:
 MIG 262

 Created on:
 03.09.2018

 Revised on:
 03.09.2018

 Valid from:
 01.10.2018

Version: 2.0 Replace version:



Section 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Substance name/trade name: MIG 262

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Plastering mortar

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier

MIG Material Innovative Gesellschaft mbH

Street/postbox

Am Grarock 3

Country/postcode/city

D-33154 Salzkotten

Technical contact point

ICT Ingenieurbüro für CHEMIE und TECHNOLOGIE Dipl.-Chem. Ing. Burkhard Brandt +49(0)5258 - 97482 – 14 ictbrandt@aol.com

Telefone/Telefax/E-Mail

+49(0)5258 - 97482 - 0 / +49(0)5258 - 97482 - 29 / E-Mail: safety@mig-mbh.de

1.4 Emergency telephone number

Poisons Information Centre University Hospital Bonn +49(0)22819240

Section 2: Potential hazards

2.1 Classification of the substances/mixtures

Classification according to Regulation (EC) No. 1272/2008 (CLP):

Eye Dam. 1; H318, Skin Irrit. 2; H315

2.2 Label elements

Labeling according to Regulation (EC) No. 1272/2008:

Pictogramm:



Signal word: Danger

Hazardous component(s) for labelling:

Portland cement (white)

Hazard warnings:

H315: Causes skin irritation. H318: Causes serious eye irritation.

Safety instructions:

P101: If medical advice is required, provide packaging or identification label.

Seite: 1 / 8

 Product:
 MIG 262

 Created on:
 03.09.2018

 Revised on:
 03.09.2018

 Valid from:
 01.10.2018

Version: 2.0 Replace version: 1.0

P102: Keep out of the reach of children. P103: Read identification label before use.

P280: Wear protective gloves / protective clothing / eye protection / face protection.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses if possible. Continue rinsing.

P332+P313: Skin irritation: Get medical advice / attention.

2.3 Other hazards:

The content of soluble chromium (VI) is not more than 0.0002% according to Annex XVII paragraph 47 of the EC Regulation 1907/2016.

Product reacts strongly alkaline with water. Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

Section 3: Composition/information on ingredients

3.2 Mixtures

Portland cement (white)

EC-No.: 266-043-4, CAS-No.: 65997-15-2

Portion: 15 - 25%

Classification according to Regulation (EC) No 1272/2008: Skin Irrit. 2; H315, Eye Dam.1; H318, STOT SE 3; H335

Substances with EU occupational exposure limit values

Quartz

EC-No.: 238-878-4, CAS-No.: 14808-60-7

Portion: 50 - 75%

(The wording of the listed risk phrases can be found in Section 16)

Section 4: First aid measures

4.1 Description of first aid measures

General information:

Remove contaminated clothing immediately.

After inhalation

Supply fresh air, consult a doctor in case of complaints.

After contact with skin

Wash immediately with soap and water

If skin irritation persists, consult a doctor.

After contact with eyes

Rinse eyes under running water for several minutes with the eyelid open. If symptoms persist, consult a doctor.

After ingestion

seek medical advice immediately.

4.2 Most important acute and delayed symptoms and effects

No further relevant information available.

4.3 Information on immediate medical help or special treatment

No further relevant information available.

Section 5: Fire-fighting measures

Seite: 2 / 8



 Product:
 MIG 262

 Created on:
 03.09.2018

 Revised on:
 03.09.2018

 Valid from:
 01.10.2018

Version: 2.0 Replace version: 1.0



5.1 Extinguishing agent

Suitable: Use fire extinguishing measures that suits the environment.

Unsuitable: Water with full jet

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Information for firefighters

Do not inhale explosion and fire gases.

Wear self-contained breathing apparatus.

Fire residues and contaminated extinguishing water must be disposed of in accordance with official regulations.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear personal protective clothing.

6.2 Environmental measures

Do not empty into drains or watercourses.

Notify the competent authority in case of release into water or sewage system.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Collect mechanically.

6.4 Reference to other sections

For information on safe handling see Section 7.

For information on personal protection see Section 8.

Section 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Avoid dust formation.

Measures to protect against fire and explosions

No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Information on storage conditions

Store in cool and dry containers in well closed containers.

Requirements for storage rooms and containers

No special requirements.

Storage class: LGK 13 Non-combustible solids

7.3 Specific end uses

Industry and sector specific guidelines

No further relevant information available.

Section 8: Exposure controls/Personal protection

8.1 Parameters to be monitored

Seite: 3 / 8

 Product:
 MIG 262

 Created on:
 03.09.2018

 Revised on:
 03.09.2018

 Valid from:
 01.10.2018

Version: 2.0 Replace version: 1.0



General dust limit value quartz

EC-No.: 238-878-4, CAS-Nr.: 14808-60-7

Specification: Occupational exposure limits in accordance with TRGS 900

Value: 1.25 mg/m³ A; 10 mg/m³ E

Peak limit: 2(II) Teratogenic: MAK

8.2 Limitation and monitoring of exposure

Personal protective equipment

General protective and hygenic measures

Do not eat, drink, smoke, or sniff while working. Take off dirty, soaked clothes immediately. Wash hands before breaks and at the end of work. Avoid contact with eyes and skin.

Eye/face protection

Tight fitting safety goggles

Skin protection

Hand gloves

With full contact:

Glove material: Nitrile rubber Layer thickness (mm): ≥4 mm

Penetration time (min.): > 480 minutes

In splash contact:

Glove material: Nitrile rubber Layer thickness (mm): ≥4 mm

Penetration time (min.): > 480 minutes

Other skin protection

butyl rubber

Fluoro rubber (Viton)

PVC gloves.

Respiratory protection

In case of dust formation, suitable respiratory protection must be worn. Filter type P2

Body protection

Work protective clothing

Limitation and monitoring of environmental exposure

See Section 6 and 7

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

- Physical state:
- Colour:
Odour:
Odourless
Odour threshold:
Not applicable

pH-value: >12

Melting point/Freezing point: No data available

Seite: 4 / 8

 Product:
 MIG 262

 Created on:
 03.09.2018

 Revised on:
 03.09.2018

 Valid from:
 01.10.2018

Version: 2.0 Replace version: 1.0



Initial boiling point and boiling Not applicable

range:

Flash point: Not applicable Evaporation rate: Not applicable

Flammability (solid, gaseous): This substance is not flammable.

upper/lower flammability or

explosive limits: Not applicable Vapour pressure: Not applicable Vapor density: Not applicable

Bulk density: $1.5 \text{ g/cm}^3 \pm 0.05 \text{ g/cm}^3$

Solubility: Fully miscible
Partition coefficient: Not applicable
n-octanol/water: Not applicable
Autoignition temperature: Not applicable
Decomposition temperature: Not specified
Viscosity: Not applicable

Explosive properties: The product / substance is not explosive.

Oxidizing properties: Not specified

9.2 Other information

No further relevant information available.

Section 10: Stability and Reactivity

10.1 Reactivity

No further relevant information available.

10.2 Chemical stability

No decomposition if used as directed.

10.3 Possibility of hazardous reactions

No dangerous reactions known.

10.4 Conditions to avoid

Avoid moisture.

10.5 Incompatible materials

No further relevant information available.

10.6 Hazardous decomposition products

No further relevant information available.

Section 11: Toxicological information

11.1 Information on toxicological effects

The mixture is not tested as such. The preparation is classified according to the conventional method (calculation method of Regulation (EC) No 1272/2008) and toxicological hazards.

Acute toxicity

Based on available data, the classification criteria are not met.

Portland cement (bright): EC-No.: 266-043-4, CAS-No.: 65997-15-2

LD₅₀ Dermal: 2000 mg/kg (rabbit) limit test, 24 hours exposure - no lethality

Skin corrosion / irritation

Causes skin irritations.

Serious eye damage / irritation

Causes severe eye damages.

Seite: 5 / 8

 Product:
 MIG 262

 Created on:
 03.09.2018

 Revised on:
 03.09.2018

 Valid from:
 01.10.2018

Version: 2.0 Replace version: 1.0



Sensitization of the respiratory tract/skin

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Specific target organ toxicity - single exposure

Based on available data, the classification criteria are not met.

Specific target organ toxicity - repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Section 12: Ecological information

12.1 Toxicity

No further relevant information available.

12.2 Persistence and degradability

No further relevant information available.

12.3 Bioaccumulative potential

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

12.5 Result of PBT and vPvB assessment

Not applicable

12.6 Other adverse effects

No further relevant information available.

Section 13: Disposal information

13.1 Waste treatment methods

Recycling by treatment or landfill according to legal and local regulations.

Treatment of contaminated packaging

Dispose according to official regulations.

Waste code according to Waste Catalog Ordinance (AVV)

101300 waste from the manufacture of cement, quicklime, gypsum and products thereof.

Seite: 6 / 8

 Product:
 MIG 262

 Created on:
 03.09.2018

 Revised on:
 03.09.2018

 Valid from:
 01.10.2018

Version: 2.0 Replace version: 1.0



Section 14: Transport information

14.1 UN-Number

Not applicable

14.2 Proper UN Shipping Name

ADR/RID

Not applicable

IMDG code / ICAO-TI / IATA-DGR

Not applicable

14.3 Transport risk classes

Not applicable

14.4 Packaging group

Not applicable

14.5 Environmental hazards

Environmentally hazardous substances

ADR/RID / IMD \underline{G} code / ICAO-TI / IATA-DGR: \square yes / \boxtimes no

Marine Pollutant: ☐ yes / ⊠no

14.6 Special precautions for the user

See sections 6 - 8

14.7 Bulk cargo transportation in accordance with Annex II of the MARPOL Convention and the IBC Code

Not applicable

Section 15: Regulatory information

15.1Safety, health and environmental regulations / legislation specific for the substance or mixture

Regulation (EC) No 2037/2000 (substances that deplete the ozone layer):

Not applicable

Regulation (EC) No 850/2004 (persistent organic pollutants):

Not applicable

Regulation (EC) No 689/2008 (export and import of dangerous chemicals):

Not applicable

Regulation (EC) No 648/2004 (Detergents Regulation):

Not applicable

Restrictions under Title VIII of Regulation (EC) No 1907/2006:

Not applicable

Water hazard class

1 slightly hazardous to water

Solvent Ordinance (31. BImSchV)

VOC proportion: 0 (calculated)

Seite: 7 / 8

 Product:
 MIG 262

 Created on:
 03.09.2018

 Revised on:
 03.09.2018

 Valid from:
 01.10.2018

Valid from: 01.10.2018
Version: 2.0 Replace version:



15.2 Chemical Safety Assessment

The mixture was not subject to safety assessment

Section 16: Other information

Changes compared to the last version

See section 1-16

Abbreviations

ADR: European Convention on the International Carriage of Dangerous Goods by Road AwSV: Ordinance on Installations for the Handling of Substances Hazardous to Water BImSchV: Ordinance for the Implementation of the Federal Emission Control Act

CAS: Chemical Abstracts Service

DIN: German Institute for Standardisation

EC: Effective Concentration EG: European Community EN: European Norm

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

PBT: Persistent, Bioaccumulative and Toxic VPvB: very Persistent and very Bioaccumulative

Methods referred to in Article 9 of Regulation (EC) No 1272/2008 were used to assess the information for classification purposes

1.0

Calculation method

Wording of the hazard statements and / or precautionary statements referred to in sections 2 to 15

Skin irrt. 2: Skin Irritating/Corrosive Effect - Category 2 Eye dam. 1: Severe eye damage/eye irritation - Category 1 H315: Causes skin irritation. H318: Causes severe eye damage.

H335: May irritate respiratory tract.

Training for employees

No training is required for activities involving this hazardous substance.

Further information

This data sheet is intended as a guideline for the proper handling of the product by trained personnel. To the best of our knowledge, the information in this safety data sheet corresponds to our knowledge at the time of printing. They do not constitute an assurance of certain product characteristics and do not establish a contractual legal relationship. It is the responsibility of the user to ensure that all information and properties are consistent with his particular application. The product is designed for a specific application, so the user himself is liable for risks and damages due to other applications. It does not release the user from knowing and using all information about the handling of the product. He is responsible for all measures regarding the use of the product.

Seite: 8 / 8